

Safety data sheet according to 1907/2006/EC, Article 31 Printing date 28.06.2023 Version number 4 (replaces version 3) Revision: 28.06.2023 SECTION 1: Identification of the substance/mixture and of the company/undertaking 1.1 Product identifier · Trade name: **Darkener Super** · Article number: 10939, 10940, 10941, 10942, 10943, 10944 M1J8-KHEQ-701T-NVC4 · UFI: · 1.2 Relevant identified uses of the substance or mixture and No further relevant information available. uses advised against · Application of the substance / the mixture Protective impregnation · 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH Tel. +49(0)911-642960 Fax. +49(0)911-644456 Lechstrasse 28

e-mail info@akemi.de

D 90451 Nürnberg · Further information obtainable from: Laboratory 1.4 Emergency telephone number: Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH Tel. +49(0)911-64296-59 Reachable during the following office hours: Monday – Thursday from 07:30 a.m. to 16:30 p.m. Friday from 07:30 a.m. to 13:30 p.m.

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

· 2.2 Label elements

•	Labelling	according	to	Regulation
	·			

- The product is classified and labelled according to the CLP regulation. (EC) No 1272/2008
- Hazard pictograms



· Signal word

Danger

P331

· Hazard-determining components of labelling: 2,2,4,6,6-pentamethylheptan Hydrocarbons, C10-C12, Isoalkanes, <2% aromatics

Hazard statements

H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways.

· Precautionary statements

- H411 Toxic to aquatic life with long lasting effects. P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- Read carefully and follow all instructions. P103
- Keep away from heat, hot surfaces, sparks, open flames and other P210 ignition sources. No smoking.
- P260 Do not breathe mist/vapours/spray.
- P273 Avoid release to the environment.
- P280 Wear protective gloves.
- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
 - Do NOT induce vomiting.



according to 1907/2006/EC, Article 31

Printing date 28.06.2023 Version number 4 (replaces version 3) Revision: 28.06.2023 Trade name: Darkener Super (Contd. of page 1) P302+P352 IF ON SKIN: Wash with plenty of water. P403+P235 Store in a well-ventilated place. Keep cool. P405 Store locked up. P501 Dispose of contents/container in accordance with local/regional/ national/international regulations. · Additional information: EUH066 Repeated exposure may cause skin dryness or cracking. · 2.3 Other hazards · Results of PBT and vPvB assessment Not applicable. · PBT: · vPvB: Not applicable. · Determination of endocrinedisrupting properties For information on endocrine disrupting properties see section 11. **SECTION 3: Composition/information on ingredients** · 3.2 Mixtures · Description: Mixture of substances listed below with nonhazardous additions. · Dangerous components: CAS: 13475-82-6 25-50% 2,2,4,6,6-pentamethylheptan EINECS: 236-757-0 Flam. Liq. 3, H226 Reg.nr.: 01-2119490725-29 Asp. Tox. 1, H304 Aquatic Chronic 4, H413 EÚH066 EC number: 923-037-2 Hydrocarbons, C10-C12, Isoalkanes, <2% aromatics 25-50% Flam. Liq. 3, H226 Asp. Tox. 1, H304 Reg.nr.: 01-2119471991-29-xxxx Aquatic Chronic 2, H411 CAS: 67-56-1 methanol <1% EINECS: 200-659-6 Flam. Liq. 2, H225 Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 Index number: 603-001-00-X STOT SE 1, H370 Reg.nr.: 01-2119433307-44 Specific concentration limits: STOT SE 1; H370: $C \ge 10$ % STOT SE 2; H371: 3 % ≤ C < 10 % CAS: 123-86-4 <1% n-butyl acetate EINECS: 204-658-1 Flam. Liq. 3, H226 STOT SE 3, H336 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29 EUH066 Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid meas	ures
· General information:	Take affected persons out into the fresh air.
	Position and transport stably in side position.
	Immediately remove any clothing soiled by the product.
· After inhalation:	Supply fresh air; consult doctor in case of complaints.
· After skin contact:	If skin irritation continues, consult a doctor.
	Immediately wash with water and soap and rinse thoroughly.
· <u>After eye contact:</u>	Rinse opened eye for several minutes under running water. Then consult a doctor.
· After swallowing:	If symptoms persist consult doctor.
• 4.2 Most important symptoms	
and effects, both acute and	
delayed	Breathing difficulty
<u>_</u>	Headache



according to 1907/2006/EC, Article 31

Printing date 28.06.2023 Version number 4 (replaces version 3) Revision: 28.06.2023 Trade name: Darkener Super (Contd. of page 2) Dizziness Dizziness Nausea Profuse sweating Hazards Danger of impaired breathing. 4.3 Indication of any immediate medical attention and special treatment needed If swallowed, gastric irrigation with added, activated carbon. **SECTION 5: Firefighting measures** · 5.1 Extinguishing media · Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. · For safety reasons unsuitable extinguishing agents: Water with full jet 5.2 Special hazards arising from the substance or mixture Formation of toxic gases is possible during heating or in case of fire. In case of fire, the following can be released: Carbon monoxide (CO) Under certain fire conditions, traces of other toxic gases cannot be excluded. • 5.3 Advice for firefighters · Protective equipment: Do not inhale explosion gases or combustion gases. Wear fully protective suit. Wear self-contained respiratory protective device. · Additional information Dispose of fire debris and contaminated fire fighting water in accordance with official regulations. Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

<u>6.1 Personal precautions</u> ,	
protective equipment and	
emergency procedures	Ensure adequate ventilation
	Keep away from ignition sources.
	Use respiratory protective device against the effects of fumes/dust/aerosol.
	Wear protective equipment. Keep unprotected persons away.
6.2 Environmental precautions:	Do not allow product to reach sewage system or any water course.
	Inform respective authorities in case of seepage into water course or sewage
	system.
	Do not allow to enter sewers/ surface or ground water.
6.3 Methods and material for	
containment and cleaning up:	Absorb with liquid-binding material (sand, diatomite, acid binders, universal
	binders, sawdust).
	Dispose contaminated material as waste according to section 13.
	Ensure adequate ventilation.
• 6.4 Reference to other sections	See Section 7 for information on safe handling.
	See Section 8 for information on personal protection equipment.
	See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe		
handling	Store in cool, dry place in tightly closed receptacles.	
		(Contd. on page 4)

EU



Safety data sheet according to 1907/2006/EC, Article 31

nting date 2	28.06.2023	Version number 4 (replaces version 3)	Revision: 28.06.202
ide name:	Darkener Super		
	E	Keep away from heat and direct sunlight. Ensure good interior ventilation, especially at floor air).	(Contd. of page r level. (Fumes are heavier tha
	l F E	Jse only in well ventilated areas. Keep receptacles tightly sealed. Ensure good ventilation/exhaustion at the workpla	ice.
		Keep ignition sources away - Do not smoke. Protect against electrostatic charges.	
	itions for safe storage, in	cluding any incompatibilities	
Storage:	ents to be met by		
	is and receptacles:	Store only in the original receptacle. Prevent any seepage into the ground.	
	n about storage in one		
		Store away from oxidising agents. Store away from foodstuffs.	
Further inf	formation about storage	Store receptacle in a well ventilated area.	
	-	Keep container tightly sealed.	
Storage cl			
7.3 Speci	fic end use(s)	No further relevant information available.	
8.1 Contro Ingredients	•	rsonal protection	
8.1 Contro Ingredients 67-56-1 m	ol parameters s with limit values that requ nethanol ong-term value: 260 mg/m ³	lire monitoring at the workplace:	
8.1 Contro Ingredients 67-56-1 m IOELV Lo Sk	ol parameters s with limit values that requ nethanol ong-term value: 260 mg/m ³	lire monitoring at the workplace:	
8.1 Contro Ingredients 67-56-1 m IOELV Lo Sk 123-86-4 r IOELV Sh	ol parameters s with limit values that requ nethanol ong-term value: 260 mg/m ³ kin	ire monitoring at the workplace: , 200 ppm	
8.1 Contro Ingredients 67-56-1 m IOELV Lo Sk 123-86-4 r IOELV Sh	ol parameters is with limit values that requ nethanol ong-term value: 260 mg/m ³ kin n-butyl acetate nort-term value: 723 mg/m ³	ire monitoring at the workplace: , 200 ppm	
8.1 Control Ingredients 67-56-1 m IOELV Lo 123-86-4 r IOELV Sh LOELV Sh LOELV Sh	ol parameters is with limit values that requine thanol ong-term value: 260 mg/m ³ kin n-butyl acetate nort-term value: 723 mg/m ³ ong-term value: 241 mg/m ³	ire monitoring at the workplace: , 200 ppm	
8.1 Control Ingredients 67-56-1 m IOELV Lo 123-86-4 r IOELV Sh IOELV Sh DNELS	ol parameters s with limit values that require thanol ong-term value: 260 mg/m ³ kin n-butyl acetate nort-term value: 723 mg/m ³ ong-term value: 241 mg/m ³ nethanol DNEL (Kurzzeit-akut)	4 mg/kg bw/day (BEV)	
8.1 Control Ingredients 67-56-1 m IOELV Lo 123-86-4 r IOELV Sr IOELV Sr DNELs 67-56-1 m Oral	ol parameters s with limit values that requ nethanol ong-term value: 260 mg/m ³ cin n-butyl acetate nort-term value: 723 mg/m ³ ong-term value: 241 mg/m ³ nethanol DNEL (Kurzzeit-akut) DNEL (Langzeit-wiederho	ire monitoring at the workplace: , 200 ppm , 150 ppm , 50 ppm 4 mg/kg bw/day (BEV) 4 mg/kg bw/day (BEV)	
8.1 Control Ingredi⊨nts 67-56-1 m IOELV Lo Sk 123-86-4 r IOELV Sh Lo DNELs 67-56-1 m	ol parameters s with limit values that require thanol ong-term value: 260 mg/m ³ kin n-butyl acetate nort-term value: 723 mg/m ³ ong-term value: 241 mg/m ³ nethanol DNEL (Kurzzeit-akut)	 <u>aire monitoring at the workplace:</u> , 200 ppm , 150 ppm , 50 ppm 4 mg/kg bw/day (BEV) 4 mg/kg bw/day (BEV) 20 mg/kg bw/day (ARB) 	
8.1 Control Ingredients 67-56-1 m IOELV Lo 123-86-4 r IOELV Sr IOELV Sr DNELs 67-56-1 m Oral	ol parameters is with limit values that requine thanol ong-term value: 260 mg/m ³ kin n-butyl acetate nort-term value: 723 mg/m ³ ong-term value: 241 mg/m ³ nethanol DNEL (Kurzzeit-akut) DNEL (Langzeit-wiederho DNEL (Kurzzeit-akut)	ire monitoring at the workplace: , 200 ppm , 150 ppm , 50 ppm 4 mg/kg bw/day (BEV) 4 mg/kg bw/day (BEV) 20 mg/kg bw/day (ARB) 4 mg/kg bw/day (BEV)	
8.1 Control Ingredients 67-56-1 m IOELV Lo 123-86-4 r IOELV Sr IOELV Sr DNELs 67-56-1 m Oral	ol parameters s with limit values that requ nethanol ong-term value: 260 mg/m ³ cin n-butyl acetate nort-term value: 723 mg/m ³ ong-term value: 241 mg/m ³ nethanol DNEL (Kurzzeit-akut) DNEL (Langzeit-wiederho	ire monitoring at the workplace: , 200 ppm , 150 ppm , 50 ppm 4 mg/kg bw/day (BEV) 4 mg/kg bw/day (BEV) 20 mg/kg bw/day (BEV) 20 mg/kg bw/day (BEV) 20 mg/kg bw/day (BEV) 20 mg/kg bw/day (ARB) 4 mg/kg bw/day (ARB)	
8.1 Contra Ingredi⊨nt: 67-56-1 m IOELV Lo Sk 123-86-4 r IOELV Sh IOELV Sh DNELs G7-56-1 m Oral Dermal	ol parameters s with limit values that requine thethanol ong-term value: 260 mg/m ³ cin n-butyl acetate nort-term value: 723 mg/m ³ ong-term value: 241 mg/m ³ ong-term value: 241 mg/m ³ DNEL (Kurzzeit-akut) DNEL (Langzeit-wiederho DNEL (Langzeit-wiederho DNEL (Langzeit-wiederho	 <u>aire monitoring at the workplace:</u> , 200 ppm , 150 ppm , 50 ppm 4 mg/kg bw/day (BEV) 4 mg/kg bw/day (BEV) 20 mg/kg bw/day (ARB) 4 mg/kg bw/day (BEV) 20 mg/kg bw/day (ARB) 4 mg/kg bw/day (ARB) 4 mg/kg bw/day (ARB) 4 mg/kg bw/day (BEV) 	
8.1 Contra Ingredi⊨nt: 67-56-1 m IOELV Lo Sk 123-86-4 r IOELV Sh IOELV Sh DNELs G7-56-1 m Oral Dermal	ol parameters is with limit values that requine thanol ong-term value: 260 mg/m ³ kin n-butyl acetate nort-term value: 723 mg/m ³ ong-term value: 241 mg/m ³ nethanol DNEL (Kurzzeit-akut) DNEL (Langzeit-wiederho DNEL (Kurzzeit-akut)	ire monitoring at the workplace: , 200 ppm , 150 ppm , 50 ppm 4 mg/kg bw/day (BEV) 4 mg/kg bw/day (BEV) 20 mg/kg bw/day (BEV) 20 mg/kg bw/day (BEV) 20 mg/kg bw/day (BEV) 20 mg/kg bw/day (ARB) 4 mg/kg bw/day (ARB)	
8.1 Contra Ingredi⊨nt: 67-56-1 m IOELV Lo Sk 123-86-4 r IOELV Sh IOELV Sh DNELs G7-56-1 m Oral Dermal	ol parameters s with limit values that requine thethanol ong-term value: 260 mg/m ³ cin n-butyl acetate nort-term value: 723 mg/m ³ ong-term value: 241 mg/m ³ ong-term value: 241 mg/m ³ DNEL (Kurzzeit-akut) DNEL (Langzeit-wiederho DNEL (Langzeit-wiederho DNEL (Langzeit-wiederho	ire monitoring at the workplace: , 200 ppm , 150 ppm , 50 ppm 4 mg/kg bw/day (BEV) 4 mg/kg bw/day (BEV) 20 mg/kg bw/day (ARB) 4 mg/kg bw/day (BEV) 20 mg/kg bw/day (BEV) 130 mg/m³ Air (ARB) 26 mg/m³ Air (BEV)	
8.1 Contra Ingredient 67-56-1 m IOELV Lo Sk 123-86-4 r IOELV Sh IOELV Sh IOELV Sh IOELS G7-56-1 m Oral Dermal Inhalative Inhalative	ol parameters s with limit values that requine thanol ong-term value: 260 mg/m ³ cin n-butyl acetate nort-term value: 723 mg/m ³ ong-term value: 241 mg/m ³ ong-term value: 241 mg/m ³ nethanol DNEL (Kurzzeit-akut) DNEL (Langzeit-wiederho DNEL (Langzeit-wiederho DNEL (Kurzzeit-akut) DNEL (Kurzzeit-akut) DNEL (Langzeit-wiederho	ire monitoring at the workplace: , 200 ppm , 150 ppm , 50 ppm 4 mg/kg bw/day (BEV) 4 mg/kg bw/day (BEV) 20 mg/kg bw/day (BEV) 20 mg/kg bw/day (ARB) 4 mg/kg bw/day (BEV) 20 mg/kg bw/day (BEV) 130 mg/m³ Air (ARB) 26 mg/m³ Air (BEV)	
8.1 Contra Ingredient 67-56-1 m IOELV Lo 123-86-4 r IOELV Sr IOELV Sr IOELV Sr IOELV Sr IOELS G7-56-1 m Oral Dermal Inhalative Inhalative	ol parameters is with limit values that requi- nethanol ong-term value: 260 mg/m ³ in n-butyl acetate nort-term value: 723 mg/m ³ ong-term value: 241 mg/m ³ nethanol DNEL (Kurzzeit-akut) DNEL (Langzeit-wiederho DNEL (Langzeit-wiederho DNEL (Kurzzeit-akut) DNEL (Langzeit-wiederho DNEL (Langzeit-wiederho DNEL (Langzeit-wiederho	 <u>aire monitoring at the workplace:</u> , 200 ppm , 150 ppm , 50 ppm , 50 ppm 4 mg/kg bw/day (BEV) 4 mg/kg bw/day (BEV) 20 mg/kg bw/day (ARB) 4 mg/kg bw/day (BEV) 20 mg/kg bw/day (BEV) 20 mg/kg bw/day (BEV) 130 mg/m³ Air (ARB) 26 mg/m³ Air (ARB) 26 mg/m³ Air (BEV) 130 mg/m³ Air (ARB) 26 mg/m³ Air (BEV) 	
8.1 Contra Ingredient 67-56-1 m IOELV Lo Sk 123-86-4 r IOELV Sh IOELV Sh IOELV Sh IOELS G7-56-1 m Oral Dermal Inhalative Inhalative	ol parameters s with limit values that requi- nethanol ong-term value: 260 mg/m ³ in n-butyl acetate nort-term value: 723 mg/m ³ ong-term value: 241 mg/m ³ ong-term value: 241 mg/m ³ ong-term value: 241 mg/m ³ ong-term value: 241 mg/m ³ DNEL (Kurzzeit-akut) DNEL (Langzeit-wiederho DNEL (Langzeit-wiederho DNEL (Langzeit-wiederho DNEL (Langzeit-wiederho DNEL (Langzeit-wiederho DNEL (Langzeit-wiederho DNEL (Langzeit-wiederho DNEL (Langzeit-wiederho	aire monitoring at the workplace: , 200 ppm a, 150 ppm, b, 50 ppm a mg/kg bw/day (BEV) 4 mg/kg bw/day (BEV) 20 mg/kg bw/day (BEV) 130 mg/m³ Air (ARB) 26 mg/m³ Air (BEV) 130 mg/m³ Air (BEV) 26 mg/m³ Air (BEV) 27 mg/kg bw/day (BEV)	
8.1 Contra Ingredi=nt 67-56-1 m IOELV Lo 123-86-4 r DNELs 67-56-1 m Oral Dermal Inhalative 123-86-4 r Oral Oral Oral Oral Oral	ol parameters s with limit values that requine thethanol ong-term value: 260 mg/m ³ cin n-butyl acetate nort-term value: 723 mg/m ³ ong-term value: 241	aire monitoring at the workplace: , 200 ppm 2, 150 ppm 50 ppm 4 mg/kg bw/day (BEV) 4 mg/kg bw/day (BEV) 20 mg/kg bw/day (BEV) 130 mg/m³ Air (ARB) 26 mg/m³ Air (BEV) 130 mg/m³ Air (BEV) 130 mg/m³ Air (BEV) 21 mg/kg bw/day (BEV) 22 mg/kg bw/day (BEV) 22 mg/kg bw/day (BEV) 22 mg/kg bw/day (BEV)	
8.1 Contra Ingredient 67-56-1 m IOELV Lo 123-86-4 r IOELV Sr IOELV Sr IOELV Sr IOELV Sr IOELS G7-56-1 m Oral Dermal Inhalative Inhalative	ol parameters s with limit values that requi- nethanol ong-term value: 260 mg/m ³ in n-butyl acetate nort-term value: 723 mg/m ³ ong-term value: 241 mg/m ³ ong-term value: 241 mg/m ³ ong-term value: 241 mg/m ³ ong-term value: 241 mg/m ³ DNEL (Kurzzeit-akut) DNEL (Langzeit-wiederho DNEL (Langzeit-wiederho DNEL (Langzeit-wiederho DNEL (Langzeit-wiederho DNEL (Langzeit-wiederho DNEL (Langzeit-wiederho DNEL (Langzeit-wiederho DNEL (Langzeit-wiederho	aire monitoring at the workplace: , 200 ppm a, 150 ppm, b, 50 ppm a mg/kg bw/day (BEV) 4 mg/kg bw/day (BEV) 20 mg/kg bw/day (BEV) 130 mg/m³ Air (ARB) 26 mg/m³ Air (BEV) 130 mg/m³ Air (BEV) 26 mg/m³ Air (BEV) 27 mg/kg bw/day (BEV)	



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.06.2023

Version number 4 (replaces version 3)

Revision: 28.06.2023

			(Contd. of page
	DNEL	(Langzeit-wiederholt)	7 mg/kg bw/day (ARB)
			3.4 mg/kg bw/day (BEV)
Inhalative	DNEL	(Kurzzeit-akut)	960 mg/m³ Air (ARB)
			859.7 mg/m³ Air (BEV)
	DNEL	(Langzeit-wiederholt)	480 mg/m³ Air (ARB)
		, ,	102.34 mg/m³ Àir (BEV)
<u>PNECs</u>			
67-56-1 m			
PNEC (wä	issrig)	100 mg/l (KA)	
		2.08 mg/l (MW)	
		20.8 mg/l (SW)	
		1,540 mg/l (WAS)	
PNEC (fes	st)	100 mg/kg Trockenge	w (BO)
•		7.7 mg/kg Trockengev	v (MWS)
		77 mg/kg Trockengew	
123-86-4 r	า-buty	acetate	
PNEC (wä	issrig)	35.6 mg/l (KA)	
		0.018 mg/l (MW)	
		0.18 mg/l (SW)	
		0.36 mg/l (WAS)	
PNEC (fes	st)	0.0903 mg/kg Trocker	ngew (BO)
,	,	0.0981 mg/kg Trockengew (MWS)	
		0.981 mg/kg Trockeng	
Additional	inform		e lists valid during the making were used as basis.
8.2 Expos			0 0
			further data; see section 7.
			s personal protective equipment
General pr	rotectiv	e and hygienic	
measures:	<u>.</u>		not eat, drink, smoke or sniff while working.
			bly solvent resistant skin cream before starting work.
			e skin protection cream for skin protection. ep away from foodstuffs, beverages and feed.
			nediately remove all soiled and contaminated clothing
			sh hands before breaks and at the end of work.
			not inhale gases / fumes / aerosols.
Respirator			er AX
Hand prote	ection		ventive skin protection by use of skin-protecting agents is recommended. er use of gloves apply skin-cleaning agents and skin cosmetics.
		Alle	and skin cosmetics.
		N.	Protective gloves
			Skin protection agent recommendation for preventive skin shel without use of protective gloves:
			STOKODERM(http://www.stoko.com) Skin protection agent recommendation for preventive skin shelter
			application and combination of protective gloves:
			STOKO EMULSION (http://www.stoko.com)
			Skin protection recommendation for skin cleaning after produ
			handling:
			FRAPANTOL (http://www.stoko.com) (Contd. on page



Printing date 28.06.2023

Safety data sheet

according to 1907/2006/EC, Article 31

Version number 4 (replaces version 3)

Revision: 28.06.2023

Trade name: Darkener Super	
	(Contd. of page 5)
	Skin protection agent recommendation for skin aftercare:
	STOKO VITAN (http://www.stoko.com)
	The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type.
	The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory anylyses of the company KCL GmbH in compliance with EN374.
	This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of
	application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL, Cmbbl, Cormany, 26124, Eichenzell,
	detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: http://www.kcl.de).
	The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
	Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
	Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
· <u>Material of gloves</u>	Fluorocarbon rubber (Viton) Nitrile rubber, NBR
	The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application
· Penetration time of glove material	to the application. Value for the permeation: Level \leq 6, 480 min The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
· For the permanent contact gloves	P
made of the following materials are	
<u>suitable:</u>	Fluorocarbon rubber (Viton) Vitoject (KCL, Art_No. 890)
	Nitrile rubber, NBR Camatril (KCL, Art_No. 730, 731, 732, 733)
· As protection from splashes gloves	
made of the following materials are	
suitable:	Nitrile rubber, NBR Camatril (KCL, 730, 731, 732, 733)
· Not suitable are gloves made of	
the following materials:	Leather gloves Strong material gloves
· Eye/face protection	Tightly sealed goggles
· Body protection:	Protective work clothing
SECTION 9: Physical and chemic	cal properties

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- · General Information
- · Colour:

Colourless



according to 1907/2006/EC, Article 31

Printing date 28.06.2023

Version number 4 (replaces version 3)

Revision: 28.06.2023

Trade name: Darkener Super

	(Contd. of page 6)
· Odour:	Characteristic
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling range	180 °C
· Lower and upper explosion limit	
· Lower:	0.6 Vol %
	7 Vol %
· Flash point:	44 °C
· Auto-ignition temperature:	240 °C
· pH	Not determined.
	Not applicable
· Viscosity:	
· Kinematic viscosity at 20 °C	11 o (DIN 52011/4)
	11 s (DIN 53211/4) Not determined.
· Dynamic:	Not determined.
· <u>Solubility</u>	Niet weie ein is en sliffige uit te weier
· water:	Not miscible or difficult to mix.
· Vapour pressure at 20 °C:	1 hPa
· Density and/or relative density	
· Density at 20 °C:	0.85 g/cm³
· 9.2 Other information	
· Appearance:	
· Form:	Fluid
· Important information on protection of health ar	nd
environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive
	air/vapour mixtures are possible.
· Solvent content:	
· Organic solvents:	59.9 %
· Solids content:	29.8 %
	23.0 /0
 Information with regard to physical hazard classes 	
· <u>Explosives</u>	Void
· Flammable gases	Void
· <u>Aerosols</u>	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases	
contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void
	T OTM

SECTION 10: Stability and reactivity

10.1 Reactivity

No further relevant information available.

AKEMI[®]

(Contd. on page 9)

FU

Page 8/13

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.06.2023 Version number 4 (replaces version 3) Revision: 28.06.2023 Trade name: Darkener Super (Contd. of page 7) · 10.2 Chemical stability · Thermal decomposition / conditions to be avoided: No decomposition if used and stored according to specifications. 10.3 Possibility of hazardous Reacts with strong oxidising agents. reactions Forms flammable gases/fumes. · 10.4 Conditions to avoid No further relevant information available. No further relevant information available. · 10.5 Incompatible materials: 10.6 Hazardous decomposition Carbon monoxide and carbon dioxide products: **SECTION 11: Toxicological information** • 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity Based on available data, the classification criteria are not met. · LD/LC50 values relevant for classification: **ATE (Acute Toxicity Estimates)** Oral LD50 50,000 mg/kg (rat) 150,000 mg/kg Dermal LD50 13475-82-6 2,2,4,6,6-pentamethylheptan Oral LD50 >5,000 mg/kg (rat) (OECD 401) Dermal LD50 2,200-2,500 mg/kg (rabbit) (OECD 402) >5 ppm (rat) Inhalative LC50/8h LC50/48h >3,193 mg/l (daphnia magna) (ISO 14559) Hydrocarbons, C10-C12, Isoalkanes, <2% aromatics >5,000 mg/kg (rat) (OECD 401) Oral LD50 LD50 >5,000 mg/kg (rabbit) (OECD 402) Dermal Inhalative LC50/8h >5 mg/l (rat) LC50/48h >1,000 mg/l (daphnia magna) (OECD 202) 67-56-1 methanol Oral LD50 100 mg/kg (rat) LD50 Dermal 15,800 mg/kg (rabbit) 300 mg/kg (rat) Inhalative LC50/4 h 128.2 mg/l (rat) 123-86-4 n-butyl acetate 10,760 mg/kg (rat) (OECD 423) Oral LD50 Dermal LD50 >14,112 mg/kg (rabbit) (OECD 402) Inhalative LC50/4 h 23.4 mg/l (rat) (OECD 403) LC50 390 mg/m3 (rat) LC50/48h 64 mg/l (Brachydanio rerio) Based on available data, the classification criteria are not met. Skin corrosion/irritation · Serious eye damage/irritation Based on available data, the classification criteria are not met. · Respiratory or skin sensitisation Based on available data, the classification criteria are not met. · Germ cell mutagenicity Based on available data, the classification criteria are not met. · Carcinogenicity Based on available data, the classification criteria are not met. · Reproductive toxicity Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. STOT-single exposure · STOT-repeated exposure Based on available data, the classification criteria are not met. Aspiration hazard May be fatal if swallowed and enters airways.



Page 9/13

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.06.2023

Version number 4 (replaces version 3)

Revision: 28.06.2023

Trade name: Darkener Super

(Contd. of page 8)

· 11.2 Information on other hazards

• Endocrine disrupting properties None of the ingredients is listed.

SECTION 12: Ecological information

•	12.1	Toxicity

· Aquatic toxicity:					
13475-82-6 2	13475-82-6 2,2,4,6,6-pentamethylheptan				
IC50/72h	>1,000 mg/l (Pseudokirchneriella subcapitata)				
EC50/48h	>1,000 mg/l (daphnia magna)				
NOELR/72h 1,000 mg/l (Pseudokirchneriella subcapitata) (OECD201)					
NOELR/21d 0.02 mg/l (daphnia magna) (OECD 211)					
NOELR/28d	0.267 mg/l (Oncorhynchus mykiss) ((Q)SAR)				
EC50/72h	>1,000 mg/l (Pseudokirchneriella subcapitata) (OECD 201)				
LC50/96h	>1,000 mg/l (Oncorhynchus mykiss) (OECD 203)				
Hydrocarbo	ns, C10-C12, Isoalkanes, <2% aromatics				
EL0/48h	1,000 mg/l (daphnia magna)				
EL0/72h	1,000 mg/l (Pseudokirchneriella subcapitata)				
LL0/96h	1,000 mg/l (Oncorhynchus mykiss)				
NOELR/72h	1,000 mg/l (Pseudokirchneriella subcapitata) (OECD 201)				
NOELR/21d	<1 mg/l (daphnia magna) (OECD 211)				
NOELR/28d	0.192 mg/l (Oncorhynchus mykiss) ((Q)SAR)				
EC50/72h	>1,000 mg/l (Pseudokirchneriella subcapitata) (OECD 201)				
LC50/96h	>1,000 mg/l (Oncorhynchus mykiss) (OECD 203)				
67-56-1 met					
EC50/96h	22,000 mg/l (Pseudokirchneriella subcapitata)				
IC50	>1,000 mg/l (BES)				
EC50/48h	>10,000 mg/l (daphnia magna)				
LC50/96h	13,500-17,600 mg/l (lem)				
	19,500-20,700 mg/l (Oncorhynchus mykiss)				
	28,200 mg/l (pimephales promelas)				
123-86-4 n-b	butyl acetate				
EC50/24h	72.8 mg/l (daphnia magna) (DIN 38412)				
EC50/96h	320 mg/l (algae)				
LC50/24h	205 mg/l (daphnia magna)				
IC50/72h	648 mg/l (Desmodesmus subspicatus)				
EC10/18h	959 mg/l (pseudomonas putida)				
EC50/48h	44 mg/l (daphnia magna)				
EC50/16h	959 mg/l (pseudomonas putida)				
NOEC	200 mg/kg (Desmodesmus subspicatus)				
NOEC/21d	23 mg/l (daphnia magna) (OECD 211)				
EC50/72h	647.7 mg/l (Desmodesmus subspicatus) (Zellvermehrungshemmtest)				
	674 mg/l (Scenedesmus subspicatus)				
LC50/96h	62 mg/l (Danio rerio.)				
	(Contd. on page 10)				



according to 1907/2006/EC, Article 31

Printing date 28.06.2023

Version number 4 (replaces version 3)

Revision: 28.06.2023

EU

Trade name: Darkener Super

(Contd. of page 9) 81 mg/l (piscis) 100 mg/l (lepomis macrochirus) 62 mg/l (Leuciscus idus) (DIN 38412) 18 mg/l (pimephales promelas) (OECD 203) 12.2 Persistence and degradability No further relevant information available. No further relevant information available. · 12.3 Bioaccumulative potential · 12.4 Mobility in soil No further relevant information available. 12.5 Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable. 12.6 Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties. · 12.7 Other adverse effects · Additional ecological information: · General notes: Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water **SECTION 13: Disposal considerations** · 13.1 Waste treatment methods Must not be disposed together with household garbage. Do not allow product to · Recommendation reach sewage system. · European waste catalogue 20 00 00 MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS 20 01 00 separately collected fractions (except 15 01) 20 01 13* solvents · Uncleaned packaging: · Recommendation: Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

· Recommended cleansing agents: Alcohol

SECTION 14: Transport information

· 14.1 UN number or ID number · ADR, IMDG, IATA	UN3295
· 14.2 UN proper shipping name · ADR	3295 HYDROCARBONS, LIQUID, N.O.S. (Hydrocarbons, C10-
	C12, Isoalkanes, <2% aromatics, 2,2,4,6,6-pentamethylheptan), ENVIRONMENTALLY HAZARDOUS
· IMDG	HYDROCARBONS, LIQUID, N.O.S. (Hydrocarbons, C10-C12, Isoalkanes, <2% aromatics, 2,2,4,6,6-pentamethylheptan),
· <u>IATA</u>	MARINE POLLUTANT HYDROCARBONS, LIQUID, N.O.S. (Hydrocarbons, C10-C12, Isoalkanes, <2% aromatics, 2,2,4,6,6-pentamethylheptan)
	(Contd. on page 11)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.06.2023

Version number 4 (replaces version 3)

Revision: 28.06.2023

Trade name: Darkener Super

	(Contd. of page
<u>14.3 Transport hazard class(es)</u>	
ADR	
AV.	
	3 (F1) Flammable liquids.
	3
· IMDG	
W .	
	2 Elementable linuida
· <u>Class</u> · Label	3 Flammable liquids. 3
· IATA	
· Class	3 Flammable liquids.
Label	3
14.4 Packing group	
· <u>ADR, IMDG, IATA</u>	III
· 14.5 Environmental hazards: · Marine pollutant:	Product contains environmentally hazardous substances: Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Flammable liquids.
· Hazard identification number (Kemler code):	30
· <u>EMS Number:</u> · Stowage Category	F-E,S-D A
• 14.7 Maritime transport in bulk according to II	
instruments	Not applicable.
Transport/Additional information:	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· <u>Transport category</u> · Tunnel restriction code	3 D/E
· <u>IMDG</u> · Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3295 HYDROCARBONS, LIQUID, N.O.
	(HYDROCARBONS, C10-C12, ISOALKANES, <2
	AROMATICS, 2,2,4,6,6-PENTAMETHYLHEPTAN), 3, III,



according to 1907/2006/EC, Article 31

Printing date 28.06.2023

Version number 4 (replaces version 3)

Revision: 28.06.2023

Trade name: Darkener Super

	(Contd. of page 11)
·	ENVIRONMENTALLY HAZARDOUS
SECTION 15: Regulatory information	ation
· 15 1 Safety, health and environm	nental regulations/legislation specific for the substance or mixture
	iental regulations/regislation specific for the substance of mixture
· <u>Directive 2012/18/EU</u> · Named dangerous substances -	
ANNEX I	None of the ingredients is listed.
· Seveso category	E2 Hazardous to the Aquatic Environment
	P5c FLAMMABLE LIQUIDS
· Qualifying quantity (tonnes) for the	
application of lower-tier requirements	200 t
· Qualifying quantity (tonnes) for the	
application of upper-tier	
	500 t
 REGULATION (EC) No 1907/2006 ANNEX XVII 	Conditions of restriction: 3, 69
	striction of the use of certain hazardous substances in electrical and electronic
equipment – Annex II	
None of the ingredients is listed.	
· REGULATION (EU) 2019/1148	
	VES PRECURSORS (Upper limit value for the purpose of licensing under Article
5(3))	
None of the ingredients is listed.	
Annex II - REPORTABLE EXPLOS	BIVES PRECURSORS
None of the ingredients is listed.	
· Regulation (EC) No 273/2004 on d	rug precursors
None of the ingredients is listed.	
Regulation (EC) No 111/2005 lavin	g down rules for the monitoring of trade between the Community and third
countries in drug precursors	
None of the ingredients is listed.	
· National regulations:	
· Information about limitation of use:	Employment restrictions concerning juveniles must be observed. Employment restrictions concerning pregnant and lactating women must be
	observed.
· Waterhazard class:	Water hazard class 1 (Self-assessment): slightly hazardous for water.
	SVHC) according to REACH, Article 57
None of the ingredients is listed.	
· VOC EU	506.2 g/l
15.2 Chemical safety	C
assessment:	A Chemical Safety Assessment has not been carried out.
SECTION 16: Other information	

This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Laboratory

(Contd. on page 13)



according to 1907/2006/EC, Article 31

Printing date 28.06.2023

Version number 4 (replaces version 3)

Revision: 28.06.2023

Trade name: Darkener Super

Data of mentions versions	(Contd. of page 12)
 Date of previous version: Version number of previous 	17.01.2023
version:	3
• <u>Abbreviations and acronyms:</u>	 RiD: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Mairtime Code for Dangerous Goods IATA: International Mairtime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 STOT SE 1: Specific target organ toxicity (single exposure) – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4